## FEDERAL ENERGY REGULATORY COMMISSION WASHINGTON, DC

OMB Control # 1902-0075 Expiration 06/30/2019

Form 556 Certification of Qualifying Facility (QF) Status for a Small Power Production or Cogeneration Facility

Pavant Solar	III PTC	ifying facility status is sought for this facility)			
1b Applicant stree 155 W. Natio	taddress inwide Blvd				
1c City		1d State/province			
Columbus		ОН			
1e Postal code 43215	1fCountry (if not United States)	1gTelephone number 614-716-1000			
1h Has the instant	facility ever previously been certified as a	QF? Yes No  x			
7i If yes, provide th	e docket number of the last known QF fili	ng pertaining to this facility: QF -			
» ·== 4··-	tification process is the applicant making				
Notice of self- (see note belo	certification  w)	Application for Commission certification (requires filing fee; see "Filing Fee" section on page 3)			
notice of self-ce	uice of self-certification does not establish	nt itself that its facility complies with the requirements for a proceeding, and the Commission does not review a "What to Expect From the Commission After You File"			
1k What type(s) of (	QF status is the applicant seeking for its fa	cility? (check all that apply)			
	all power production facility status	1/			
	What is the purpose and expected effective date(s) of this filing?				
<ul> <li>Original certifi</li> </ul>	* Original certification; facility expected to be installed by 12/31/16 and to begin operation on 12/31/16				
Change(s) to a	Change(s) to a previously certified facility to be effective on				
	(identify type(s) of change(s) below, and describe change(s) in the Miscellaneous section starting on page 19)				
Name char	ge and/or other administrative change(s)				
Change in	ownership				
Change(s) a	affecting plant equipment, fuel use, powe	r production capacity and/or cogeneration thermal output			
	correction to a previous filing submitted o				
(describe the su	upplement or correction in the Miscellane	ous section starting on page 19)			
1m If any of the following three statements is true, check the box(es) that describe your situation and complete the to the extent possible, explaining any special circumstances in the Miscellaneous section starting on page 19.					
Previously gr	acility complies with the Commission's QF anted by the Commission in an order date Miscellaneous section starting on page 19	requirements by virtue of a waiver of certain regulations ed (specify any other relevant waiver 9)			
The instant fa	icility would comply with the Commission with this application is granted	n's QF requirements if a petition for waiver submitted			
employment	Of Unique of Innovative technologies not	gulations, but has special circumstances, such as the contemplated by the structure of this form, that make or impossible (describe in Misc. section starting on p. 19)			

FE	RC Form 556			Page 6- All Facilities		
	2a Name of contact person  Benjamin E. Duckworth			<b>2b</b> Telephone number 614-583-7453		
li .	2c Which of the following describes the contact person's relationship to the applicant? (check one)					
				rized to represent the applicant		
6	l <u> </u>		• •	sent the applicant on this matter		
äŧ				, ,		
Lawyer, consultant, or other representative authorized to represent the applicant on this matter  2d Company or organization name (if applicant is an individual, check here and skip to line 2e)						
Infor	id skip to line 2e)					
Contact Information	2e Street address (if same as Applica 155 W. Nationwide Blvd	ent, check here and skip t	o line 3a) ;			
U	2f City Columbus	n deret	2g State/prov	vince		
	2h Postal code 43215	2iCountry (if not United	States)	11.2 11		
	3a Facility name		8			
£:						
ß	3b Street address (if a street address	does not exist for the fac	ility, check here	and skip to line 3c)		
으	1920 W 8900N					
멀						
ty Identification and Location	3c Geographic coordinates: If you indicated that no street address exists for your facility by checking the box in line 3b, then you must specify the latitude and longitude coordinates of the facility in degrees (to three decimal places). Use the following formula to convert to decimal degrees from degrees, minutes and seconds: decimal degrees = degrees + (minutes/60) + (seconds/3600). See the "Geographic Coordinates" section on page 4 for help. If you provided a street address for your facility in line 3b, then specifying the geographic coordinates below is optional.					
ä	Longitude East (+)	degrees	Latitude	North (+)		
岁	West (-)			South (-) degrees		
iity	3d City (if unincorporated, check her Fillmore	re and enter nearest city)	☐ Je State/p	province		
Facilit	3f County (or check here for indep	pendent 3	g Country (If no	t United States)		
ഥ	Millard			,		
Identify the electric utilities that are contemplated to transact with the facility.						
lities	4a Identify utility interconnecting with the facility Page (Ci Copp					
Transacting Utilities	4b Identify utilities providing wheeling service or check here if none 🗶					
nsacti	PacifiCorp via Rocky Mou	ntain Power	,			
Trai	4d Identify utilities providing supple service or check here if none 🗷	mentary power, backup	power, mainten a	nce power, and/or interruptible power		

Pavent Solar III LLC

FERC Form 556 Page 7- All Facilities 5a Direct ownership as of effective date or operation date; Identify all direct owners of the facility holding at least 10 percent equity interest. For each identified owner, also (1) indicate whether that owner is an electric utility, as defined in section 3(22) of the Federal Power Act (16 U.S.C. 796(22)), or a holding company, as defined in section 1262(8) of the Public Utility Holding Company Act of 2005 (42 U.S.C. 16451(8)), and (2) for owners which are electric utilities or holding companies, provide the percentage of equity interest in the facility held by that owner. If no direct owners hold at least 10 percent equity interest in the facility, then provide the required information for the two direct owners with the largest equity interest in the facility. Electric utility or If Yes. Full legal names of direct owners holding % equity company Interest 1) Pavant Solar IMI LLC 2) 11 \_\_\_\_\_\_ No 🗔 3) 5) No [ 7) No [ 8) No 🗔 Ownership and Operation 9) Yes No Check here and continue in the Miscellaneous section starting on page 19 if additional space is needed 5b Upstream (i.e., indirect) ownership as of effective date or operation date: Identify all upstream (i.e., indirect) owners of the facility that both (1) hold at least 10 percent equity interest in the facility, and (2) are electric utilities, as defined in section 3(22) of the Federal Power Act (16 U.S.C. 796(22)), or holding companies, as defined in section 1262(8) of the Public Utility Holding Company Act of 2005 (42 U.S.C. 16451(8)). Also provide the percentage of equity interest in the facility held by such owners. (Note that, because upstream owners may be subsidiaries of one another, total percent equity interest reported may exceed 100 percent.) Check here if no such upstream owners exist. Full legal names of electric utility or holding company upstream owners % equity 1) AEP Renewables, :LLC 100% 2) AEP Energy Supply LLC 100% 3) American Electric Power Company, Inc. 100% 6) ..... 9) Check here and continue in the Miscellaneous section starting on page 19 If additional space is needed 5c Identify the facility operator

FE	_	orm 556							Page 8- All Facilitie
	ба	Describe	the primary e	nergy input: (check o	ne main (	ategory and, if	applicable,	one subcatego	ry)
		☐ Biom	ass (specify)		🖪 Rene	wable resource	es (specify)	Geother	rnal
			Landfill gas			Hydro power	- river	Fossil fu	el (specify)
i			Manure dige	-		Hydro power	- tidal	□ C	oal (not waste)
			Municipal so	ld waste		Hydro power	-wave	☐ Ft	ıel oil/diesel
			Sewage dige	ster gas		Solar - photov	roltaic	□ N	atural gas (not waste)
			Wood			Solar - therma	ıl		ther fossil fuel
		L	Other bioma:	ss (describe on page	19) 🗀	Wind			lescribe on page 19)
				below in line 6b)	_ [	Other renewa (describe on p	oage 19)		escribe on page 19)
	бb	If you spo	ecified "waste"	as the primary energ	jy Input ii	i line 6a, Indica	te the type o	f waste fuel us	ed: (check one)
k .		☐ Wa	ste fuel listed i	n 10 C.F.R. § 292,202(	b) (specif	y one of the fol	llowing)		
			Anthracite of	ulm produced prior	to July 23	, 1985			
			Anthracite in ash content	efuse that has an ave of 45 percent or mor	rage hea re	t content of 6,0	000 Btu or les	s per pound ar	d has an average
		۲	Bituminous average ash	coal refuse that has a content of 25 percer	n averag nt or more	e heat content e	of 9,500 Btu	per pound or l	ess and has an
Input		Γ	(BLM) or the	om subbituminous co to be waste by the U t is located on non-F nt shows that the latte	nited Sta ederal or	tes Departmen non-Indian lan	t of the inter ds outside of	ior's Bureau of f BLM's iurisdict	Land Management
Energy Input			」 BLM or that	produced on Federal is located on non-Fe ows that the latter is	deral or r	ion-Indian land	Is outside of	Bl M's iurisdicti	on provided that
		Г	Lignite prod as a result o	uced in association v such a mining opera	vith the p ition	roduction of m	ontan wax a	nd lignite that	becomes exposed
		Γ	_ CU91)	ls (except natural gas			(descri	be on page 19)	
		C	J C.P.K. 9 2.40	al gas from gas or oil O for waste natural ga with 18 C.F.R. § 2,400	as; includ	scribe on page e with your filtr	19 how the	gas meets the l lals necessary t	equirements of 18 o demonstrate
	V.		Materials th	at a government age	ncy has c	ertified for disp	osal by comb	oustion (descri	be on page 19)
7		Ŀ	Heat from e	othermic reactions (	describe	on page 19)		esidual heat (c	lescribe on page 19)
	ì		Used rubber	tires $\square$ Plast	ic materl	als 🗆	Refinery off	-gas [	Petroleum coke
		(	ity industry (d	y Input that has little escribe in the Miscell value and existence	an <del>e</del> ous se	ection starting o	on nage 19- i	nclude a discus	f the qualifying sion of the fuel's
	бс	energy in	puts, and prov	rgy input, calculated ide the related perce or natural gas fuel, us	ntage of t	the total avera	ae annual en	OFITY IDOUT TO 1	ollowing fossil fuel he facility (18 C.F.R. §
			-	uel	Annual	average energ		Percentage of t	
			Natural gas	<u></u>	input fo	or specified fue	1	nnual energy i	-
			Oil-based fu	es -		-	0 Btu/h	* * *	0. %
			Coal	-			O Btu/h O Btu/h		0.%
	_			<u> </u>			· Btu/n		() %

Indicate the maximum gross and maximum net electric power production causacity of the facility at the point(s) of

FERC Form 556

Page 9- All Facilities

7a The maximum gross power production capacity at the terminals of the individual generator(s) under the most favorable anticipated design conditions		2	5,780	<sup>o</sup> kw
The Parasitic station power used at the facility to run equipment which is necessary and integral to the power production process (boiler feed pumps, fans/blowers, office or maintenance buildings directly related to the operation of the power generating facility, etc.). If this facility includes non-power production processes (for instance, power consumed by a cogeneration facility's thermal host), do not include any power consumed by the non-power production activities in your reported parasitic station power.				
7c Electrical losses in interconnection transformers			1,33	ķŅ
			215	› kW
7d Electrical losses in AC/DC conversion equipment, if any				
	31		800°,	) kW
7e Other interconnection losses in power lines or facilities (other than transformers and AC/DC conversion equipment) between the terminals of the generator(s) and the point of interconnection				
with the utility			45	kW
7f Total deductions from gross power production capacity = $7b + 7c + 7d + 7e$			1.01.0	· k\w
7g Maximum net power production capacity = 7a - 7f	Γ-			
		19,	(د رود که و	kW

7h Description of facility and primary components: Describe the facility and its operation. Identify all boilers, heat recovery steam generators, prime movers (any mechanical equipment driving an electric generator), electrical generators, photovoltaic solar equipment, fuel cell equipment and/or other primary power generation equipment used in the facility. Descriptions of components should include (as applicable) specifications of the nominal capacities for mechanical output, electrical output, or steam generation of the identified equipment. For each piece of equipment identified, clearly indicate how many pieces of that type of equipment are included in the plant, and which components are normally operating or normally in standby mode. Provide a description of how the components operate as a system. Applicants for cogeneration facilities do not need to describe operations of systems that are clearly depicted on and easily understandable from a cogeneration facility's attached mass and heat balance diagram; however, such applicants should provide any necessary description needed to understand the sequential operation of the facility depicted in their mass and heat balance diagram. If additional space is needed, continue in the Miscellaneous section starting on page 19.

Pavant Solar III will utilize 81,840 multi-crystalline silicoe modules each with a nameplace power capacity of 315 Watts supplied by Jinkosolar (81,840 x 315W -25.78 MWdc). The 315W modules are configured in strings of 20 modulos (6,300 Wdc) and mounted due high in portrait orientation on forizontal single-axis tracking arrays. The arrays will be oriented lengthwise along a north-south axis with 13.0 feet of spacing from one row to the next. The strings will then flow to one of 16 DC combiner boxes each of which will be rared for 350A and have a total capacity for 24 fused inputs (15A, 1000Vdc). Fiftcon primary DC combiner boxes will hold 24 strings (each string with 20 modules at 315W each). One secondary DC combiner will hold 12 strings. The DC combiner boxes will then flow into one of 11 TMEIC Solar ware Samurai PVL-L1833GRM inverters. Each inverter has a capacity rating of 1,818 kW AC. Each inverter will be supplied from 7,440 315W modules with an aggregate nameplace capacity of 2,343.6 kW DC, for a DC to AC ratio of 1.289. Each "Power Station" consists of a single inverter atop a concrete pad with a medium-voltage transformer designed to raise the inverter output voltage from 418V AC to the internal project distribution voltage of 34.5kV. A main step transformer will raise the project output to the interconnection voltage of 46kV. Annual production should amount to approximately 52,528,000kWh.

Page 10- Small Power Production Facilities

## Information Required for Small Power Production Facility

If you indicated in line 1k that you are seeking qualifying small power production facility status for your facility, then you must respond to the items on this page. Otherwise, skip page 10.

	oin mis bage.	Outerwise, skip page 10.		
nce	Pursuant to 18 C.F.R. § 292.204(a) with the power production capad resource, are owned by the same megawatts. To demonstrate confrom this size limitation under the (Pub. L. 101-575, 104 Stat. 2834 (1 through 8e below (as applicable).  8a Identify any facilities with electing and the instant facility, at least a 5 percent equity interesting.	person(s) or its affiliates, appliance with this size limite Solar, Wind, Waste, and 1990) as amended by Pub.  ctrical generating equipment for which any of the ett.	wer production facilities that us and are located at the same site tation, or to demonstrate that y Geothermal Power Production L. 102-46, 105 Stat. 249 (1991))	e the same energy e, may not exceed 80 your facility is exempt Incentives Act of 1990 respond to lines 8a
	Cireck Refe if NB SUCH Facilities exis	St.		
Certification of Compliance with Size Limitations	Facility location (city or county, state)	Root docket # (if any)	Common owner(s)	Maximum net power
or Ital	1)	QF -		kW
E E	2)	QF -		kW
e —	3)	QF -		
tification with Size		•		kW
T Sat	Check here and continue in t	he Miscellaneous section	starting on page 19 if additiona	space is needed
	Yes (continue at line 8c b) 8c Was the original notice of self- before December 31, 1994? Yes 8d Dld construction of the facility 8e If you answered No in line 8d, the facility, taking Intolaccount all provide a brief narrative explanatio (in particular, describe why constructoward completion of the facility.	certification or application No commence on or before indicate whether reasona factors relevant to construction in the Miscellaneous se	December 31, 1999? Yes  ble diligence was exercised towaction? Yes No	No vard the completion of If you answered Yes,
Certification of Compliance with Fuel Use Requirements	Pursuant to 18 C.F.R. § 292.204(b), amounts, for only the following purevention of unanticipated equip the public health, safety, or welfare used for these purposes may not experiod beginning with the date the garden of compliance with	rposes: Ignition; start-up, ment outages; and allevia s, which would result from xceed 25 percent of the to e facility first produces ele	testing; flame stabilization; contion or prevention of emergen a electric power outages. The a potal energy input of the facility of the energy or any calendar year.	ntrol use; alleviation or cies, directly affecting mount of fossil fuels during the 12-month ar thereafter.
ion o Use I	Applicant certifies that the			
ertificat th Fuel	i in percent of the lotal energy	amount of fossil fuel used	at the facility will not, in aggre	
vith with	facility first produces electri	c energy or any calendar	year thereafter,	ng with the date the

## General Cogeneration

FERC Form 556

Page 11- Cogeneration Facilities

## Information Required for Cogeneration Facility

If you indicated in line 1k that you are seeking qualifying cogeneration facility status for your facility, then you must respond to the items on pages 11 through 13. Otherwise, skip pages 11 through 13.

Pursuant to 18 C.F.R. § 292.202(c), a cogeneration facility produces electric energy and forms of useful thermal energy (such as heat or steam) used for industrial, commercial, heating, or cooling purposes, through the sequential use of energy. Pursuant to 18 C.F.R. § 292.202(s), "sequential use" of energy means the following: (1) for a toppingcycle cogeneration facility, the use of reject heat from a power production process in sufficient amounts in a thermal application or process to conform to the requirements of the operating standard contained in 18 C.F.R. § 292.205(a); or (2) for a bottoming-cycle cogeneration facility, the use of at least some reject heat from a thermal application or process for power production.

10a What type(s) of cogeneration technology does the facility represent? (check all that apply)

Topping-cycle cogeneration

Bottoming-cycle cogeneration

10b To help demonstrate the sequential operation of the cogeneration process, and to support compliance with other requirements such as the operating and efficiency standards, include with your filing a mass and heat balance diagram depicting average annual operating conditions. This diagram must include certain items and meet certain requirements, as described below. You must check next to the description of each requirement below to certify that you have complied with these requirements.

Check to certify compliance with indicated requirement

Requirement

Diagram must show orientation within system plping and/or ducts of all prime movers, heat recovery steam generators, boilers, electric generators, and condensers (as applicable), as well as any other primary equipment relevant to the cogeneration process.

Any average annual values required to be reported in lines 10b, 12a, 13a, 13b, 13d, 13f, 14a, 15b, 15d and/or 15f must be computed over the anticipated hours of operation.

Diagram must specify all fuel inputs by fuel type and average annual rate in Btu/h. Fuel for supplementary firing should be specified separately and clearly labeled. All specifications of fuel inputs should use lower heating values.

Diagram must specify average gross electric output in kW or MW for each generator.

Diagram must specify average mechanical output (that is, any mechanical energy taken off of the shaft of the prime movers for purposes not directly related to electric power generation) in horsepower, if any. Typically, a cogeneration facility has no mechanical output.

At each point for which working fluid flow conditions are required to be specified (see below), such flow condition data must include mass flow rate (in lb/h or kg/s), temperature (in °F, R, "C or K), absolute pressure (in psia or kPa) and enthalpy (in Btu/lb or kJ/kg). Exception: For systems where the working fluid is liquid only(no vapor at any point in the cycle) and where the type of liquid and specific heat of that liquid are clearly indicated on the diagram or in the Miscellaneous section starting on page 19, only mass flow rate and temperature (not pressure and enthalpy) need be specified. For reference, specific heat at standard conditions for pure liquid water is approximately 1.002 Btu/ (lb\*R) or 4.195 kJ/(kg\*K),

Diagram must specify working fluid flow conditions at Input to and output from each steam turbine or other expansion turbine or back-pressure turbine.

Diagram must specify working fluid flow conditions at delivery to and return from each thermal application.

Diagram must specify working fluid flow conditions at make-up water inputs.

Page 12- Cogeneration Facilities

EPAct 2005 cogeneration facilities: The Energy Policy Act of 2005 (EPAct 2005) established a new section 210(n) of the Public Utility Regulatory Policies Act of 1978 (PURPA), 16 USC B24a-3(n), with additional requirements for any qualifying cogeneration facility that (1) is seeking to sell electric energy pursuant to section 210 of PURPA and (2) was either not a cogeneration facility on August 8, 2005, or had not filed a self-certification or application for Commission certification of QF status on or before February 1, 2006. These requirements were implemented by the whether these additional requirements apply to your cogeneration facility and, if so, whether your facility complies with such requirements.

11a Was your facility operating as a qualifying cogeneration facility on or before August 8, 2005? Yes: No

11b Was the Initial filing seeking certification of your facility (whether a notice of self-certification or an application for Commission certification) filed on or before February 1, 20067 Yes No

if the answer to either line 11a or 11b is Yes, then continue at Ilne 11c below. Otherwise, if the answers to both lines 11a and 11b are No, skip to line 11e below.

11c With respect to the design and operation of the facility, have any changes been implemented on or after February 2, 2006 that affect general plant operation, affect use of thermal output, and/or increase net power production capacity from the plant's capacity on February 1, 2006?

Yes (continue at line 11d below)

No. Your facility is not subject to the requirements of 18 C.F.R. § 292.205(d) at this time. However, it may be subject to to these requirements in the future if changes are made to the facility. At such time, the applicant would need to recertly the facility to determine eligibility. Skip lines 11d through 11j.

11d Does the applicant contend that the changes identified in line 11c are not so significant as to make the facility a "new" cogeneration facility that would be subject to the 18 C.F.R. § 292.205(d) cogeneration requirements?

Yes. Provide in the Miscellaneous section starting on page 19 a description of any relevant changes made to the facility (including the purpose of the changes) and a discussion of why the facility should not be considered a "new" cogeneration facility in light of these changes. Skip lines 11e through 11].

No. Applicant stipulates to the fact that it is a "new" cogeneration facility (for purposes of determining the applicability of the requirements of 18 C.F.R. § 292.205(d)) by virtue of modifications to the facility that were initiated on or after February 2, 2006. Continue below at line 11e.

11e Will electric energy from the facility be sold pursuant to section 210 of PURPA?

Yes. The facility is an EPAct 2005 cogeneration facility. You must demonstrate compliance with 18 C.F.R. § 292.205(d)(2) by continuing at line 11f below.

No. Applicant certifies that energy will *not*be sold pursuant to section 210 of PURPA. Applicant also certifies its understanding that it must recertify its facility in order to determine compliance with the requirements of 18 C.F.R. § 292-205(d) *before* elling energy pursuant to section 210 of PURPA in the future. Skip lines 11f through 11j.

1 If Is the net power production capacity of your cogeneration facility, as Indicated in line 7g above, less than or equal to 5,000 kW?

Yes, the net power production capacity is less than or equal to 5,000 kW. 18 C.F.R. § 292.205(d)(4) provides a rebuttable presumption that cogeneration facilities of 5,000 kW and smaller capacity comply with the requirements for fundamental use of the facility's energy output in 18 C.F.R. § 292.205(d)(2). Applicant certifies its understanding that, should the power production capacity of the facility increase above 5,000 kW, then the facility must be recertified to (among other things) demonstrate compliance with 18 C.F.R. § 292.205(d)(2). Skip lines 11g through 11j.

No, the net power production capacity is greater than 5,000 kW. Demonstrate compliance with the requirements for fundamental use of the facility's energy output in 18 C.F.R. § 292.205(d)(2) by continuing on the next page at line 11g.

# EPAct 2005 Requirements for Fundamental Use of Energy Output from Cogeneration Facilities (continued)

FERC Form 556

Page 13- Cogeneration Facilities

Lines 11g through 11k below gulde the applicant through the process of demonstrating compliance with the requirements for "fundamental use" of the facility's energy output. 18 C.F.R. § 292.205(d)(2). Only respond to the lines on this page if the instructions on the previous page direct you to do so. Otherwise, skip this page.

18 C.F.R. § 292.205(d)(2) requires that the electrical, thermal, chemical and mechanical output of an EPAct 2005 cogeneration facility is used fundamentally for industrial, commercial, residential or institutional purposes and is not intended fundamentally for sale to an electric utility, taking into account technological, efficiency, economic, and variable thermal energy requirements, as well as state laws applicable to sales of electric energy from a qualifying facility to its host facility. If you were directed on the previous page to respond to the Items on this page, then your facility is an EPAct 2005 cogeneration facility that is subject to this "fundamental use" requirement.

The Commission's regulations provide a two-pronged approach to demonstrating compliance with the requirements for fundamental use of the facility's energy output. First, the Commission has established in 18 C.F.R. § 292.205(d)(3) a "fundamental use test" that can be used to demonstrate compliance with 18 C.F.R. § 292.205(d)(2). Under the fundamental use test, a facility is considered to comply with 18 C.F.R. § 292.205(d)(2) if at least 50 percent of the facility's total annual energy output (including electrical, thermal, chemical and mechanical energy output) is used for industrial, commercial, residential or institutional purposes.

Second, an applicant for a facility that does not pass the fundamental use test may provide a narrative explanation of and support for its contention that the facility nonetheless meets the requirement that the electrical, thermal, chemical and mechanical output of an EPAct 2005 cogeneration facility is used fundamentally for industrial, commercial, residential or institutional purposes and is not intended fundamentally for sale to an electric utility, taking into account technological, efficiency, economic, and variable thermal energy requirements, as well as state laws applicable to sales of electric energy from a qualifying facility to its host facility.

Complete lines 11g through 11j below to determine compliance with the fundamental use test in 18 C.F.R. § 292.205(d)(3). Complete lines 11g through 11j even if you do not intend to rely upon the fundamental use test to demonstrate compliance with 18 C.F.R. § 292.205(d)(2).

11g Amount of electrical, thermal, chemical and mechanical energy output (net of Internal generation plant losses and parasitic loads) expected to be used annually for industrial, commercial, residential or institutional purposes and not sold to an electric utility	. 350
11h Total amount of electrical, thermal, chemical and mechanical energy expected to be sold to an electric utility	MWI
11i Percentage of total annual energy output expected to be used for industrial, commercial, residential or institutional purposes and not sold to a utility = 100 * 11g /(11g + 11h)	MW
11) is the response in line 11) greater than or equal to 50 percent?	. "

Yes. Your facility complies with 18 C.F.R. § 292.205(d)(2) by virtue of passing the fundamental use test provided in 18 C.F.R. § 292.205(d)(3). Applicant certifies its understanding that, if it is to rely upon passing the fundamental use test as a basis for complying with 18 C.F.R. § 292.205(d)(2), then the facility must comply with the fundamental use test both in the 12-month period beginning with the date the facility first produces electric energy, and in all subsequent calendar years.

No. Your facility does not pass the fundamental use test. Instead, you must provide In the Miscellaneous section starting on page 19 a narrative explanation of and support for why your facility meets the requirement that the electrical, thermal, chemical and mechanical output of an EPAct 2005 cogeneration facility is used fundamentally for industrial, commercial, residential or institutional purposes and is not intended fundamentally for sale to an electric utility, taking into account technological, efficiency, economic, and variable thermal energy requirements, as well as state laws applicable to sales of electric energy from a QF to its host facility. Applicants providing a narrative explanation of why their facility should be found to comply with 18 C.F.R. § 292.205(d)(2) in spite of non-compliance with the fundamental use test may want to review paragraphs 47 through 61 of Order No. 671 (accessible from the Commission's QF website at www.ferc.gov/QF), which provide discussion of the facts and circumstances that may support their explanation. Applicant should also note that the percentage reported above will establish the standard that that facility must comply with, both for the 12-month period beginning with the date the facility first produces electric energy, and in all subsequent calendar years. SeeOrder No. 671 at paragraph 51. As such, the applicant should make sure that it reports appropriate values on lines 11g and 11h above to serve as the relevant annual standard, taking into account expected variations in production conditions.

Page 14- Topping-Cycle Cogeneration Facilities

Average annual rate of

## Information Required for Topping-Cycle Cogeneration Facility

If you indicated in line 10a that your facility represents topping-cycle cogeneration technology, then you must respond to the items on pages 14 and 15. Otherwise, skip pages 14 and 15.

The thermal energy output of a topping-cycle cogeneration facility is the net energy made available to an industrial or commercial process or used in a heating or cooling application. Pursuant to sections 292.202(c), (d) and (h) of the Commission's regulations (18 C.F.R. §§ 292.202(c), (d) and (h)), the thermal energy output of a qualifying topping-cycle cogeneration facility must be useful. In connection with this requirement, describe the thermal output of the topping-cycle cogeneration facility by responding to lines 12a and 12b below.

12a Identify and describe each thermal host, and specify the annual average rate of thermal output made available to each host for each use. For hosts with multiple uses of thermal output, provide the data for each use in separate rows.

	Name of entity (thermal host) taking thermal output	Thermal host's relationship to facility: Thermal host's use of thermal outout	thermal output attributable to use (net of heat contained in process return or make-up water)
1)		Select thermal host's relationship to facility	
-		Select thermal host's use of thermal output	Btu/h,
2)		Select thermal host's relationship to facility	
<b> </b>		Select thermal host's use of thermal output	Btu/h
3)		Select thormal host's relationship to facility	
-	-	Select thermal host's use of therma outnut	Btu/h
4)		Select thermal host's relationship to facility	
_		Select thermal host's use of therma, output	Btu/h
5)		Select thermal host's relationship to facility	
		Select thermal host's use of therma output	Btu/lt_
6)		Select <u>thermal ho</u> st's re <u>lationship to</u> facility	121
	V	Select thermal <u>host's use</u> of ther <u>mal ou</u> rout	Bu./b

Check here and continue in the Miscellaneous section starting on page 19 if additional space is needed

12b Demonstration of usefulness of thermal output: At a minimum, provide a brief description of each use of the thermal output identified above. In some cases, this brief description is sufficient to demonstrate usefulness. However, if your facility's use of thermal output is not common, and/or if the usefulness of such thermal output is not reasonably clear, then you must provide additional details as necessary to demonstrate usefulness. Your application may be rejected and/or additional information may be required if an insufficient showing of usefulness is made. (Exception: If you have previously received a Commission certification approving a specific use of thermal output related to the instant facility, then you need only provide a brief description of that use and a reference by date and docket number to the order certifying your facility with the indicated use. Such exemption may not be used if any change creates a material deviation from the previously authorized use.) If additional space is needed, continue in the Miscellaneous section starting on page 19.

Usefulness of Topping-Cycle Thermal Output

## Topping-Cycle Operating and Efficiency Value Calculation

FERC Form 556

## Page 15-Topping-Cycle Cogeneration Facilities

Applicants for facilities representing topping-cycle technology must demonstrate compliance with the topping-cycle operating standard and, if applicable, efficiency standard. Section 292.205(a)(1) of the Commission's regulations (18 C.F.R. § 292.205(a)(1)) establishes the operating standard for topping-cycle cogeneration facilities: the useful thermal energy output must be no less than 5 percent of the total energy output. Section 292.205(a)(2) (18 C.F.R. § 292.205(a)(2)) establishes the efficiency standard for topping-cycle cogeneration facilities for which installation commenced on or after March 13, 1980: the useful power output of the facility plus one-half the useful thermal energy output must (A) be no less than 42.5 percent of the total energy input of natural gas and oil to the facility; and (B) if the useful thermal energy output is less than 15 percent of the total energy output of the facility, be no less than 45 percent of the total energy input of natural gas and oil to the facility. To demonstrate compliance with the topping-cycle operating and/or efficiency standards, or to demonstrate that your facility is exempt from the efficiency standard based on the date that installation commenced, respond to lines 13a through 13l below.

If you indicated in line 10a that your facility represents bothtopping-cycle and bottoming-cycle cogeneration technology, then respond to lines 13a through 13l below considering only the energy inputs and outputs attributable to the topping-cycle portion of your facility. Your mass and heat balance diagram must make clear which mass and energy flow values and system components are for which portion (topping or bottoming) of the cogeneration system.

13a Indicate the annual average rate of useful thermal energy output made available to the host(s), net of any heat contained in condensate return or make-up water	
13b Indicate the annual average rate of net electrical energy output	Ruch
13c Multiply line 13b by 3,412 to convert from kW to Btu/h	kW
	<u>\ Btu/</u> h
13d Indicate the annual average rate of mechanical energy output taken directly off of the shaft of a prime mover for purposes not directly related to power production (this value is usually zero)	
13e Multiply line 13d by 2,544 to convert from hp to Btu/h	<u>ho</u>
126	Btu/h
13f Indicate the annual average rate of energy Input from natural gas and oil	1110-541.
13g Topping-cycle operating value = 100 * 13a / (13a + 13c + 13e)	Btu/h
12h T	J 96
13h Topping-cycle efficiency value = 100 * (0.5*13a + 13c + 13e) / 13f	
12: Compliance with a constitution of a deal to the	0 %
13i Compliance with operating standard: Is the operating value shown in line 13g greater than	or equal to 5%?
Yes (complies with operating standard)  No (does not comply with operating standard)	ting standard)

13) Did installation of the facility in its current form commence on or after March 13, 1980?

Yes. Your facility is subject to the efficiency requirements of 18 C.I.R. § 292.205(a)(2). Demonstrate compliance with the efficiency requirement by responding to line 13k or 13l, as applicable, below.

No. Your facility is exempt from the efficiency standard. Skip lines 13k and 13l.

13k Compliance with efficiency standard (for low operating value): If the operating value shown in line 13g is less than 15%, then Indicate below whether the efficiency value shown in line 13h greater than or equal to 45%:

Yes (complies with efficiency standard)

No (does not comply with efficiency standard)

13I Compliance with efficiency standard (for high operating value): If the operating value shown in line 13g is greater than or equal to 15%, then indicate below whether the efficiency value shown in line 13h is greater than or equal to 42.5%:

Yes (complies with efficiency standard)

No (does not comply with efficiency standard)

Page 16-Bottoming-Cycle Cogeneration Facilities

## Information Required for Bottoming-Cycle Cogeneration Facility

If you indicated in line 10a that your facility represents bottoming-cycle cogeneration technology, then you must respond to the items on pages 16 and 17. Otherwise, skip pages 16 and 17.

the Commission's regulations (1)	pottoming-cycle cogeneration facility is the energy rel heat is then used for power production. Pursuant to s B C.F.R. § 292.202(c) and (e)), the thermal energy outp be useful. In connection with this requirement, descri is used for power production by responding to lines 14.	sections 292.20 ut of a qualifyi	02(c) and (e) o ng bottoming	
14a Identify and describe each thermal host and each bottoming-cycle cogeneration prohost. For hosts with multiple bottoming-cycle cogeneration processes, provide the separate rows.		process engage he data for eac	ocess engaged in by each data for each process in	
Name of entity (thermal hose performing the process from which at least some of the reject heat Is used for power production	m :	the therm augmented of increa production	nergy input to nal host been d for purpose ising power on capacity? cribe on p. 19	
1)	Select thermal host's relationship to facility Select thermal host's process type	Yes	No	
2)	Select thermal host's relationship to facility Select thermal host's process type	Yes	No	
3)	Select thermal host's relationship to facility  Select thermal host's process type	Yes	No	

Check here and continue in the Miscellaneous section starting on page 19 if additional space is needed

14b Demonstration of usefulness of thermal output: At a minimum, provide a brief description of each process identified above. In some cases, this brief description is sufficient to demonstrate usefulness. However, if your facility's process is not common, and/or if the usefulness of such thermal output is not reasonably clear, then you must provide additional details as necessary to demonstrate usefulness. Your application may be rejected and/or additional information may be required if an insufficient showing of usefulness is rnade. (Exception: if you have previously received a Commission certification approving a specific bottoming-cycle process related to the instant facility, then you need only provide a brief description of that process and a reference by date and docket number to the order certifying your facility with the Indicated process. Such exemption may not be used if any material changes to the process have been made.) If additional space is needed, continue in the Miscellaneous section starting on page 19.

Usefulness of Bottoming-Cycle

Bottoming-Cycle Operating and

Efficiency Value Calculation

## Page 17- Bottoming-Cycle Cogeneration Facilities

Applicants for facilities representing bottoming-cycle technology and for which installation commenced on or after March 13, 1990 must demonstrate compliance with the bottoming-cycle efficiency standards. Section 292.205(b) of the Commission's regulations (18 C.F.R. § 292.205(b)) establishes the efficiency standard for bottoming-cycle cogeneration facilities: the useful power output of the facility must be no less than 45 percent of the energy input of natural gas and oil for supplementary firing. To demonstrate compliance with the bottoming-cycle efficiency standard (if applicable), or to demonstrate that your facility is exempt from this standard based on the date that installation of the facility began, respond to lines 15a through 15h below.

BRYAN CAVE LLP

If you indicated in line 10a that your facility represents both topping-cycle and bottoming-cycle cogeneration technology, then respond to lines 15a through 15h below considering only the energy inputs and outputs attributable to the bottoming-cycle portion of your facility. Your mass and heat halance diagram must make clear which mass and energy flow values and system components are for which portion of the cogeneration system (topping or bottoming),

15a Did installation of the facility in its current form commence on or after March 13, 1980?

Yes. Your facility is subject to the efficiency requirement of 18 C.J.R. § 292.205(b). Demonstrate compliance with the efficiency requirement by responding to lines 15b through 15h below.

No. Your facility is exempt from the efficiency standard. Skip the rest of page 17.

15b Indicate the annual average rate of net electrical energy output	
	kW
15c Multiply line 15b by 3,412 to convert from kW to Btu/h	
	Bru/h
15d Indicate the annual average rate of mechanical energy output taken directly off of the shaft of a prime mover for purposes not directly related to power production (this value is usually zero)	
	ha
15e Multiply line 15d by 2,544 to convert from hp to Btu/h	
_ 0 0	^ Btu/h
15f Indicate the annual average rate of supplementary energy Input from natural gas	
or oil	<u>Btu</u> /h
15g Bottoming-cycle efficiency value = 100 * (15c + 15e) / 15f	
N V	46

15h Compliance with efficiency standard: Indicate below whether the efficiency value shown in line 15g is greater than or equal to 45%;

Yes (complies with efficiency standard)

No (does not comply with efficiency standard)

Page 18- All Facilities

## Certificate of Completeness, Accuracy and Authority

Applicant must certify compliance with and understanding of filing requirements by checking next to each item below and signing at the bottom of this section. Forms with incomplete Certificates of Completeness, Accuracy and Authority will be rejected by the Secretary of the Commission.

Signer identified below certifies the following: (check all items and applicable subitems)

He or she has read the filing, including any information contained in any attached documents, such as cogeneration mass and heat balance diagrams, and any information contained in the Miscellaneous section starting on page 19, and knows its contents. He or she has provided all of the required information for certification, and the provided information is true as stated. to the best of his or her knowledge and belief. He or she possess full power and authority to sign the filling; as required by Rule 2005(a)(3) of the Commission's Rules of Practice and Procedure (18 C.F.R, § 385.2005(a)(3)), he or she is one of the following: (check one)  $\square$  The person on whose behalf the filing is made An officer of the corporation, trust, association, or other organized group on behalf of which the filing is made An officer, agent, or employe of the governmental authority, agency, or instrumentality on behalf of which the filing is made A representative qualified to practice before the Commission under Rule 2101 of the Commission's Rules of Practice and Procedure (18 C.F.R. § 385.2101) and who possesses authority to sign He or she has reviewed all automatic calculations and agrees with their results, unless otherwise noted in the Miscellaneous section starting on page 19. He or she has provided a copy of this Form 556 and all attachments to the utilities with which the facility will interconnect and transact (see lines 4a through 4d), as well as to the regulatory authorities of the states in which the facility and those utilities reside. See the Required Notice to Public Utilities and State Regulatory Authorities section on page 3 for more information.

Provide your signature, address and signature date below. Rule 2005(c) of the Commission's Rules of Practice and Procedure (18 C.F.R. § 385.2005(c)) provides that persons filing their documents electronically may use typed characters representing his or her name to sign the filed documents. A person filing this document electronically should sign (by typing his or her name) in the space provided below.

Your Signature	Your address	Date
Amanda Riggs Conner	801 Pennsylvania Ave. NW, Ste. 7 Washington, D.C. 20004	3 '5
Audit Notes	H 15 10 10 10 10 10 10 10 10 10 10 10 10 10	
Commission Staff Use Only:		

Page 19- All Facilities

## Miscellaneous

Use this space to provide any information for which there was not sufficient space in the previous sections of the form to provide. For each such item of Information clearly identify the line number that the information belongs to. You may also use this space to provide any additional information you believe is relevant to the certification of your facility.

Your response below is not limited to one page. Additional page(s) will automatically be inserted into this form if the length of your response exceeds the space on this page. Use as many pages as you require.